

www.update-adtex.com

PRODUCT CATALOG



M-SERIES

A-SERIES

G-SERIES

- EXCELLENT
- EFFICIENT
- ELECTRONIC

U UPDATE TOUCH LTD

PRODUCT FEATURES



SPRING HYDRAULIC SHOCK
ABSORBER REAR SUSPENSION



INDEPENDENT SPRING FRONT
SUSPENSION



KDS MOTOR 48V 3.7KW-5KW(DC & AC)



CURTIS CONTROLLER 48V 275A
(DC & AC)



TROJAN BATTERY T-875, 6*8V



ITALY GRAZIANO TRANSAXLE



ALUMINUM CHASSIS



SPECIAL DESIGN BATTERY TRAY



UNIQUE E-KEY



DISC BRAKE



ELECTROMAGNETIC BRAKE



PRODUCT SERIES





MODEL: M1S2

DIMENSION:	2380 * 1120 * 1900 MM
F/R TRACK:	900 / 1000 MM
WHEELBASE:	1650 MM
GROUND CLEARANCE:	114 MM
MIN. TURNING RADIUS:	2.9 M
NET WEIGHT:	430 KG
PAY LOAD:	360 KG
CLIMBING CAPACITY {FULL LOAD}:	30%
CHASSIS:	ALUMINUM CHASSIS
BODY COVER:	PP ENGINEERING PLASTIC
MAX.FORWARD SPEED:	35 KM/H
RANGE:	80-100KM

CONFIGURATION

MOTOR:	KDS 48V 3KW ACIM MOTOR
CONTROLLER:	CURTIS CONTROLLER 48V 350A
BATTERIES:	TROJAN T-875 6*8V
CHARGER:	48V 17A REGULATOR

CHASSIS CONFIGURATION

RANSAXLE:	ITALY GRAZIANO AXLE
BRAKE SYSTEM:	REAR SELF-ADJUSTING DRUM BRAKE
STEERING SYSTEM:	DUAL SELF-ADJUSTING RACK & PINION
F/R SUSPENSION:	MCPHERSON INDEPENDENT SPRING SUSPENSION
TYRE:	215/35-12 TYRE



MODEL: M1S2+2

DIMENSION:	3200 * 1200 * 2000 MM
F/R TRACK:	860 / 970 MM
WHEELBASE:	1670 MM
GROUND CLEARANCE:	150 MM
MIN.TURNING RADIUS:	2.9 M
NET WEIGHT:	400 KG
PAY LOAD:	400 KG
CLIMBING CAPACITY {FULL LOAD}:	30%
CHASSIS:	ALUMINUM CHASSIS
BODY COVER:	PP ENGINEERING PLASTIC
MAX.FORWARD SPEED:	35 KM/H
RANGE:	80-100KM

CONFIGURATION

MOTOR:	ADC 48V 5KW ACIM MOTOR
CONTROLLER:	CURTIS CONTROLLER 48V 350A
BATTERIES:	TROJAN T-875 6*8V
CHARGER:	48V 20A INTELLIGENT ONBOARD CHARGER

CHASSIS CONFIGURATION

TRANSAXLE:	ITALY GRAZIANO AXLE
BRAKE SYSTEM:	REAR SELF-ADJUSTING DRUM BRAKE
STEERING SYSTEM:	DUAL SELF-ADJUSTING RACK & PINION
F/R SUSPENSION:	MCPHERSON INDEPENDENT SPRING SUSPENSION
TYRE:	215/35-12 TYRE



MODEL: M1S4

DIMENSION:	3100 * 1120 * 1900 MM
F/R TRACK:	900 / 1000 MM
WHEELBASE:	2490 MM
GROUND CLEARANCE:	114 MM
MIN. TURNING RADIUS:	2.9 M
NET WEIGHT:	500 KG
PAY LOAD:	360 KG
CLIMBING CAPACITY {FULL LOAD}:	30%
CHASSIS:	ALUMINUM CHASSIS
BODY COVER:	PP ENGINEERING PLASTIC
MAX.FORWARD SPEED:	35 KM/H
RANGE:	80-100KM

CONFIGURATION

MOTOR:	KDS 48V 5KW ACIM MOTOR
CONTROLLER:	CURTIS CONTROLLER 48V 350A
BATTERIES:	TROJAN T-875 6*8V
CHARGER:	48V 17A REGULATOR

CHASSIS CONFIGURATION

TRANSAXLE:	ITALY GRAZIANO AXLE
BRAKE SYSTEM:	REAR SELF-ADJUSTING DRUM BRAKE
STEERING SYSTEM:	DUAL SELF-ADJUSTING RACK & PINION
F/R SUSPENSION:	MCPHERSON INDEPENDENT SPRING SUSPENSION
TYRE:	215/35-12 TYRE



MODEL: M1S4+2

DIMENSION:	3400 * 1120 * 1900 MM
F/R TRACK:	900 / 1000 MM
WHEELBASE:	2540 MM
GROUND CLEARANCE:	114 MM
MIN.TURNING RADIUS:	2.9 M
NET WEIGHT:	630 KG
PAY LOAD:	360 KG
CLIMBING CAPACITY (FULL LOAD):	30%
CHASSIS:	ALUMINUM CHASSIS
BODY COVER:	PP ENGINEERING PLASTIC
MAX.FORWARD SPEED:	35 KM/H
RANGE:	80-100KM

CONFIGURATION

MOTOR:	KDS 48V 5KW ACIM MOTOR
CONTROLLER:	CURTIS CONTROLLER 48V 350A
BATTERIES:	TROJAN T-875 6*8V
CHARGER:	48V 17A REGULATOR

CHASSIS CONFIGURATION

TRANSAXLE:	ITALY GRAZIANO AXLE
BRAKE SYSTEM:	REAR SELF-ADJUSTING DRUM BRAKE
STEERING SYSTEM:	DUAL SELF-ADJUSTING RACK & PINION
F/R SUSPENSION:	MCPHERSON INDEPENDENT SPRING SUSPENSION
TYRE:	215/35-12 TYRE



MODEL: M1S6+2

DIMENSION:	4000 * 1200 * 1900 MM
F/R TRACK:	860 / 970 MM
WHEELBASE:	3300 MM
GROUND CLEARANCE:	114 MM
MIN.TURNING RADIUS:	5.1 M
NET WEIGHT:	630 KG
PAY LOAD:	500 KG
CLIMBING CAPACITY {FULL LOAD}:	20%
CHASSIS:	STEEL CHASSIS
BODY COVER:	PP ENGINEERING PLASTIC
MAX.FORWARD SPEED:	24 KM/H
RANGE:	50-70 KM

CONFIGURATION

MOTOR:	ADC SEPARATELY EXCITED MOTOR 48V 3.7KW
CONTROLLER:	CURTIS CONTROLLER 48V 350A
BATTERIES:	TROJAN T-875 6*8V
CHARGER:	48V 17A REGULATOR

CHASSIS CONFIGURATION

TRANSAXLE:	ITALY GRAZIANO AXLE
BRAKE SYSTEM:	REAR SELF-ADJUSTING DRUM BRAKE
STEERING SYSTEM:	DUAL SELF-ADJUSTING RACK & PINION
F/R SUSPENSION:	MCPHERSON INDEPENDENT SPRING SUSPENSION
TYRE:	215/40R12 TYRE



MODEL: M1H2

DIMENSION:	3500 * 1150 * 1935 MM
F/R TRACK:	890 / 990 MM
WHEELBASE:	2260 MM
GROUND CLEARANCE:	114 MM
MIN. TURNING RADIUS:	2.9 M
NET WEIGHT:	560 KG
PAY LOAD:	600 KG
CLIMBING CAPACITY {FULL LOAD}:	30%
CHASSIS:	ALUMINUM CHASSIS
BODY COVER:	PP ENGINEERING PLASTIC
MAX. FORWARD SPEED:	35 KM/H
RANGE:	80-100KM

CONFIGURATION

MOTOR:	KDS 48V 5KW ACIM MOTOR
CONTROLLER:	CURTIS CONTROLLER 48V 350A
BATTERIES:	TROJAN T-875 6*8V
CHARGER:	48V 17A REGULATOR

CHASSIS CONFIGURATION

TRANSAXLE:	ITALY GRAZIANO AXLE
BRAKE SYSTEM:	REAR SELF-ADJUSTING DRUM BRAKE
STEERING SYSTEM:	DUAL SELF-ADJUSTING RACK & PINION
F/R SUSPENSION:	MCPHERSON INDEPENDENT SPRING SUSPENSION
TYRE:	215/35-12 TYRE



MODEL: A1H2/CC

DIMENSION:	3400 * 1200 * 1900 MM
F/R TRACK:	860 / 970 MM
WHEELBASE:	2310 MM
GROUND CLEARANCE:	114 MM
MIN.TURNING RADIUS:	3.6 M
NET WEIGHT:	660 KG
PAY LOAD:	600 KG
CLIMBING CAPACITY {FULL LOAD}:	20%
CHASSIS:	STEEL CHASSIS
BODY COVER:	PP ENGINEERING PLASTIC
MAX.FORWARD SPEED:	24 KM/H
RANGE:	60-80 KM

CONFIGURATION

MOTOR:	ADC SEPARATELY EXCITED MOTOR 48V 3.7KW
CONTROLLER:	CURTIS CONTROLLER 48V 350A
BATTERIES:	TROJAN T-875 6*8V
CHARGER:	48V 17A REGULATOR

CHASSIS CONFIGURATION

TRANSAXLE:	ITALY GRAZIANO AXLE
BRAKE SYSTEM:	REAR SELF-ADJUSTING DRUM BRAKE
STEERING SYSTEM:	DUAL SELF-ADJUSTING RACK & PINION
F/R SUSPENSION:	MCPHERSON INDEPENDENT SPRING SUSPENSION
TYRE:	205/50-10 TYRE



MODEL: A1H2/EC

DIMENSION:	4000 * 1200 * 1900 MM
F/R TRACK:	860 / 970 MM
WHEELBASE:	3300 MM
GROUND CLEARANCE:	114 MM
MIN.TURNING RADIUS:	5.1 M
NET WEIGHT:	800 KG
PAY LOAD:	300 KG
CLIMBING CAPACITY {FULL LOAD}:	20%
CHASSIS:	STEEL CHASSIS
BODY COVER:	PP ENGINEERING PLASTIC
MAX.FORWARD SPEED:	23 KM/H
RANGE:	40-60KM

CONFIGURATION

MOTOR:	ADC 48V 5KW ACIM MOTOR
CONTROLLER:	CURTIS AC CONTROLLER 48V 350A
BATTERIES:	TROJAN T-875 6*8V
CHARGER:	48V 17A REGULATOR

CHASSIS CONFIGURATION

TRANSAXLE:	ITALY GRAZIANO AXLE
BRAKE SYSTEM:	REAR SELF-ADJUSTING DRUM BRAKE
STEERING SYSTEM:	DUAL SELF-ADJUSTING RACK & PINION
F/R SUSPENSION:	MCPHERSON INDEPENDENT SPRING SUSPENSION
TYRE:	205/50-10 TYRE



MODEL: A1H2/LC

DIMENSION:	3400 * 1200 * 1800 MM
F/R TRACK:	860 / 970 MM
WHEELBASE:	2300 MM
GROUND CLEARANCE:	114 MM
MIN.TURNING RADIUS:	3.6 M
NET WEIGHT:	750 KG
PAY LOAD:	600 KG (DOWN) / 300 KG (UP)
CLIMBING CAPACITY {FULL LOAD}:	25%
CHASSIS:	STEEL CHASSIS
BODY COVER:	PP ENGINEERING PLASTIC
MAX.FORWARD SPEED:	24 KM/H
RANGE:	50-70KM
CARGO SIZE :	1200 * 1700 * 250 MM

CONFIGURATION

MOTOR:	ADC SEPARATELY EXCITED MOTOR 48V 3.7KW
CONTROLLER:	CURTIS CONTROLLER 48V 350A
BATTERIES:	TROJAN T-875 6*8V
CHARGER:	48V 17A REGULATOR

CHASSIS CONFIGURATION

TRANSAXLE:	ITALY GRAZIANO AXLE
BRAKE SYSTEM:	REAR SELF-ADJUSTING DRUM BRAKE
STEERING SYSTEM:	DUAL SELF-ADJUSTING RACK&PINION
F/R SUSPENSION:	MCPHERSON INDEPENDENT SPRING SUSPENSION
TYRE:	205/50-10 TYRE



MODEL: G1P5

DIMENSION:	3200 * 1500 * 2100 MM
F/R TRACK:	1100 / 1150 MM
WHEELBASE:	1990 MM
GROUND CLEARANCE:	190 MM
MIN.TURNING RADIUS:	4.1 M
NET WEIGHT:	800 KG
PAY LOAD:	560 KG
CLIMBING CAPACITY {FULL LOAD}:	25%
CHASSIS:	ALUMINUM CHASSIS
BODY COVER:	WHOLE METAL BODY
MAX.FORWARD SPEED:	35 KM/H
RANGE:	60-80KM

CONFIGURATION

MOTOR:	KDS 72V 5KW ACIM MOTOR
CONTROLLER:	CURTIS AC CONTROLLER 48V 350A
BATTERIES:	TROJAN T-105 8*6V
CHARGER:	48V 25A INTELLIGENT ONBOARD CHARGER

CHASSIS CONFIGURATION

TRANSAXLE:	HEAVY DUTY AXLE WITH DIFFERENTIAL GEAR
BRAKE SYSTEM:	FOUR WHEEL HYDRAULIC DISC BRAKE
STEERING SYSTEM:	DUAL SELF-ADJUSTING RACK & PINION
F/R SUSPENSION:	MCPHERSON INDEPENDENT SPRING SUSPENSION
TYRE:	185/70R13 TYRE



MODEL: G1S8

DIMENSION:	3950 * 1500 * 2000 MM
F/R TRACK:	1210 / 1200 MM
WHEELBASE:	2100 MM
GROUND CLEARANCE:	170 MM
MIN.TURNING RADIUS:	4.3 M
NET WEIGHT:	1100 KG
PAY LOAD:	750 KG
CLIMBING CAPACITY {FULL LOAD}:	25%
CHASSIS:	HIGH STRENGTH STEEL ALLOY FRAME WITH E-COATING & POWDER COATING
BODY COVER:	ABS PLASTIC
MAX.FORWARD SPEED:	40 KM/H
RANGE:	60-80KM

CONFIGURATION

MOTOR:	KDS 72V 7.5KW ACIM MOTOR
CONTROLLER:	CURTIS AC CONTROLLER 72V 350A
BATTERIES:	TROJAN T-875 9*8V
CHARGER:	72V 30A INTELLIGENT ONBOARD CHARGER

CHASSIS CONFIGURATION

TRANSAXLE:	HEAVY DUTY AXLE WITH DIFFERENTIAL GEAR
BRAKE SYSTEM:	VACUUM BOOSTER HYDRAULIC BRAKE
STEERING SYSTEM:	EPS (ELECTRIC POWER STEERING) SYSTEM
F/R SUSPENSION:	MCPHERSON INDEPENDENT SPRING SUSPENSION
TYRE:	175/60R14 TYRE



MODEL: G1S11

DIMENSION:	4500 * 1500 * 2000 MM
F/R TRACK:	1210 / 1200 MM
WHEELBASE:	2100 MM
GROUND CLEARANCE:	170 MM
MIN.TURNING RADIUS:	4.3 M
NET WEIGHT:	1000 KG
PAY LOAD:	850 KG
CLIMBING CAPACITY {FULL LOAD}:	25%
CHASSIS:	HIGH STRENGTH STEEL ALLOY FRAME WITH E-COATING & POWDER COATING ABS PLASTIC
BODY COVER:	
MAX.FORWARD SPEED:	40 KM/H
RANGE:	60-80KM

CONFIGURATION

MOTOR:	KDS 72V 7.5KW ACIM MOTOR
CONTROLLER:	CURTIS AC CONTROLLER 72V 350A
BATTERIES:	TROJAN T-875 9*8V
CHARGER:	72V 30A INTELLIGENT ONBOARD CHARGER

CHASSIS CONFIGURATION

TRANSAXLE:	HEAVY DUTY AXLE WITH DIFFERENTIAL GEAR
BRAKE SYSTEM:	VACUUM BOOSTER HYDRAULIC BRAKE
STEERING SYSTEM:	EPS (ELECTRIC POWER STEERING) SYSTEM
F/R SUSPENSION:	MCPHERSON INDEPENDENT SPRING SUSPENSION
TYRE:	175/60R14 TYRE



MODEL: G1S2H

DIMENSION:	4100 * 1500 * 2000 MM
F/R TRACK:	1210 / 1200 MM
WHEELBASE:	2100 MM
GROUND CLEARANCE:	170 MM
MIN.TURNING RADIUS:	4.3 M
NET WEIGHT:	1390 KG
PAY LOAD:	800 KG
CLIMBING CAPACITY (FULL LOAD):	25%
CHASSIS:	HIGH STRENGTH STEEL ALLOY FRAME WITH E-COATING & POWDER COATING
BODY COVER:	ABS PLASTIC
MAX.FORWARD SPEED:	40 KM/H
RANGE:	60-80KM
CARGO SIZE :	2450 * 1450 *1200MM

CONFIGURATION

MOTOR:	KDS 72V 7.5KW ACIM MOTOR
CONTROLLER:	CURTIS AC CONTROLLER 72V 350A
BATTERIES:	TROJAN T-875 9*8V
CHARGER:	72V 30A INTELLIGENT ONBOARD CHARGER

CHASSIS CONFIGURATION

TRANSAXLE:	HEAVY DUTY AXLE WITH DIFFERENTIAL GEAR
BRAKE SYSTEM:	VACUUM BOOSTER HYDRAULIC BRAKE
STEERING SYSTEM:	EPS (ELECTRIC POWER STEERING) SYSTEM
F/R SUSPENSION:	MCPHERSON INDEPENDENT SPRING SUSPENSION
TYRE:	175/60R14 TYRE

CUSTOMIZATION PARTS



ALUMINUM RIM



CURTIS 840 GAUGE



CLOCK



CD PLAYER



STAINLESS STEEL STORAGE



SUN SHADE



RAIN CURTAIN



SAFE GUARD



SAFE BELT



CARGO BOX



TOWING TRAILER



CADDIE PLATE



GOLF PLAYER KITS



SEAT COVER



STICKER

www.update-adtex.com

20/F, Champion Building,
287-291 Des Voeux Road Central,
Sheung Wan, Hong Kong.

Tel: (852) 2854 2812

Fax: (852) 2544 6452

E-mail: nettec04@yahoo.com



- EXCELLENT
- EFFICIENT
- ELECTRONIC

U UPDATE TOUCH LTD